



Beny 4 Guns DC EV Charging Station

120kW-480kW



Datasheet


Zhejiang Benyi New Energy Co.,Ltd.
Shuanghuanglou Industrial Zone, Beibaixiang Yueqing,zhejiang P.R. China
TEL: +86-577-5717 7008 FAX: +86-577-5717 7007
✉ info@evb.com 🏠 Importer:xxxxxxx
🌐 www.evb.com 📍 Address:xxxxxxx
♻️ This catalogue has been printed on ecological paper .
© Zhejiang Benyi New Energy Co., Ltd. All rights reserved.
⚠️ If the models and specifications in this product catalogue change due to product updates, we will not provide prior notification.



WWW.EVB.COM

Product Overview

The Beny DC EV Charging Station boasts two remarkable 7-inch touch screens for effortless control. It offers powerful comprehensive protection features. With convenient app control and Ethernet/4G/WiFi connectivity, you can charge your EV with confidence and efficiency.



Product Advantages

- IP55 Rating
- 4G
- Full Protection
- OCPP 1.6J
- 7-inch Touch Screens
- RFID
- APP Control

Model Selection

DC EV Charging Station		BDC120-F	BDC150-F	BDC160-F
				
Structure Description				
Shell Material	Galvanized Sheet			
Dimension	800*900*1900(L*W*H mm)			
Packing Dimension	1050*1250*2160(L*W*H mm)			
Weight	≤380kG	≤395kG	≤400kG	
Installation Method	Floor-stand Type			
Cable Routing	Bottom Inlet Wiring,Up Outlet Wiring			
Total length of gun cable	5 m			
Charging Outlets	Quadruple(A+B+C+D) (A:CCS1/CCS2/GBT/CHADEMO/NACS) (B:CCS1/CCS2/GBT/CHADEMO/NACS) (C:CCS1/CCS2/GBT/CHADEMO/NACS) (D:CCS1/CCS2/GBT/CHADEMO/NACS)			
Connectivity Authorization	RFID, App			
Screen	2*(7 Inch LCD Screen/LED Light)			
Electrical Specification				
AC Input Voltage	AC380V-415V, 3P+N+PE			
Rated Input Current	204A	228A	244A	
Input Frequency	50Hz/60Hz			
Consumption	≤24W			
Rated Power	120kW	150kW	160kW	
Output Voltage Range	CCS1/CCS2/NACS/GBT: 150Vdc ~ 1000Vdc;CHADEMO: 150Vdc ~ 500Vdc			
Output Current	CCS1/CCS2/NACS/GBT:0~250A;CHADEMO:0~125A			
Efficiency	≥95%			
Power Factor	≥0.99(load:100%)			

Functionate Design	
User Interface	Emergency Stop Button,LED Indicator,Card Swiping,Touch Screen
Charging Stands	EN IEC 61851-1: 2019, IEC 61851-1: 2017, EN 61851-23: 2014, IEC 61851-23: 2014, EN 61851-24: 2014, IEC 61851-24: 2014, EN IEC 61000-6-2: 2019, EN IEC 61000-6-4:2019, EN IEC 61851-21-2: 2021
Communication	
OCPP	OCPP 1.6J
Network Interface	Ethernet/4G/WiFi
RF Parameters	
LTE-FDD Operating Frequency	B1/B2/B3/B4/B5/B7/B8/B12/B13/B18/B19/B20/B25/B26/B28
LTE-TDD Operating Frequency	B38/B39/B40/B41
UMTS Operating Frequency	B1/B2/B4/B5/B6/B8/B19
MIFARE Operating Frequency	13.56MHz±7K
2.4G WI-FI Operating Frequency	2412MHz-2484MHz
2.4G WI-FI Maximum Transmit Power	20.5 dBm
WCDMA Maximum Transmit Power	24 dBm +1/-3 dB
LTE-FDD Maximum Transmit Power	23 dBm±2 dB
LTE-TDD Maximum Transmit Power	23 dBm±2 dB
MIFARE Maximum Transmit Power	14.05dBuA/m
Environment Condition	
Application Place	Indoor/Outdoor
Working Altitude	<2000m
Storage Temperature	-30℃~+85℃
Working Temperature	-30℃~+50℃
Working Humidity	5%~95%
Protection Level	IP55 IK10(Screen IK08)
Natural Cooling	Forced-air Cooling
Security Design	Over/Under Voltage Protection, Overload Protection, Current Leakage Protection, Grounding Protection, Over Temp Protection, Lightening Surge Protection

Model Selection

DC EV Charging Station		BDC180-F	BDC200-F	BDC210-F
				
Structure Description				
Shell Material		Galvanized Sheet		
Dimension		800*900*1900(L*W*H mm)		
Packing Dimension		1050*1250*2160(L*W*H mm)		
Weight		≤415kG	≤430kG	≤435kG
Installation Method		Floor-stand Type		
Cable Routing		Bottom Inlet Wiring,Up Outlet Wiring		
Total length of gun cable		5 m		
Charging Outlets		Quadruple(A+B+C+D) (A:CCS1/CCS2/GBT/CHADEMO/NACS) (B:CCS1/CCS2/GBT/CHADEMO/NACS) (C:CCS1/CCS2/GBT/CHADEMO/NACS) (D:CCS1/CCS2/GBT/CHADEMO/NACS)		
Connectivity Authorization		RFID, App		
Screen		2*(7 Inch LCD Screen/LED Light)		
Electrical Specification				
AC Input Voltage		AC380V-415V, 3P+N+PE		
Rated Input Current		274A	304A	320A
Input Frequency		50Hz/60Hz		
Consumption		≤24W		
Rated Power		180kW	200kW	210kW
Output Voltage Range		CCS1/CCS2/NACS/GBT: 150Vdc ~ 1000Vdc;CHADEMO: 150Vdc ~ 500Vdc		
Output Current		CCS1/CCS2/NACS/GBT:0~250A;CHADEMO:0~125A		
Efficiency		≥95%		
Power Factor		≥0.99(load:100%)		

Functionate Design	
User Interface	Emergency Stop Button,LED Indicator,Card Swiping,Touch Screen
Charging Stands	EN IEC 61851-1: 2019, IEC 61851-1: 2017, EN 61851-23: 2014, IEC 61851-23: 2014, EN 61851-24: 2014, IEC 61851-24: 2014, EN IEC 61000-6-2: 2019, EN IEC 61000-6-4:2019, EN IEC 61851-21-2: 2021
Communication	
OCPP	OCPP 1.6J
Network Interface	Ethernet/4G/WiFi
RF Parameters	
LTE-FDD Operating Frequency	B1/B2/B3/B4/B5/B7/B8/B12/B13/B18/B19/B20/B25/B26/B28
LTE-TDD Operating Frequency	B38/B39/B40/B41
UMTS Operating Frequency	B1/B2/B4/B5/B6/B8/B19
MIFARE Operating Frequency	13.56MHz±7K
2.4G WI-FI Operating Frequency	2412MHz-2484MHz
2.4G WI-FI Maximum Transmit Power	20.5 dBm
WCDMA Maximum Transmit Power	24 dBm +1/-3 dB
LTE-FDD Maximum Transmit Power	23 dBm±2 dB
LTE-TDD Maximum Transmit Power	23 dBm±2 dB
MIFARE Maximum Transmit Power	14.05dBuA/m
Environment Condition	
Application Place	Indoor/Outdoor
Working Altitude	<2000m
Storage Temperature	-30℃~+85℃
Working Temperature	-30℃~+50℃
Working Humidity	5%~95%
Protection Level	IP55 IK10(Screen IK08)
Natural Cooling	Forced-air Cooling
Security Design	Over/Under Voltage Protection, Overload Protection, Current Leakage Protection, Grounding Protection, Over Temp Protection, Lightening Surge Protection

Model Selection

DC EV Charging Station		BDC240-F	BDC270-F	BDC280-F
				
Structure Description				
Shell Material	Galvanized Sheet			
Dimension	800*900*1900(L*W*H mm)			
Packing Dimension	1050*1250*2160(L*W*H mm)			
Weight	≤450kG	≤465kG	≤470kG	
Installation Method	Floor-stand Type			
Cable Routing	Bottom Inlet Wiring,Up Outlet Wiring			
Total length of gun cable	5 m			
Charging Outlets	Quadruple(A+B+C+D) (A:CCS1/CCS2/GBT/CHADEMO/NACS) (B:CCS1/CCS2/GBT/CHADEMO/NACS) (C:CCS1/CCS2/GBT/CHADEMO/NACS) (D:CCS1/CCS2/GBT/CHADEMO/NACS)			
Connectivity Authorization	RFID, App			
Screen	2*(7 Inch LCD Screen/LED Light)			
Electrical Specification				
AC Input Voltage	AC380V-415V, 3P+N+PE			
Rated Input Current	365A	411A	426A	
Input Frequency	50Hz/60Hz			
Consumption	≤24W			
Rated Power	240kW	270kW	280kW	
Output Voltage Range	CCS1/CCS2/NACS/GBT: 150Vdc ~ 1000Vdc;CHADEMO: 150Vdc ~ 500Vdc			
Output Current	CCS1/CCS2/NACS/GBT:0~250A;CHADEMO:0~125A			
Efficiency	≥95%			
Power Factor	≥0.99(load:100%)			

Functionate Design	
User Interface	Emergency Stop Button,LED Indicator,Card Swiping,Touch Screen
Charging Stands	EN IEC 61851-1: 2019, IEC 61851-1: 2017, EN 61851-23: 2014, IEC 61851-23: 2014, EN 61851-24: 2014, IEC 61851-24: 2014, EN IEC 61000-6-2: 2019, EN IEC 61000-6-4:2019, EN IEC 61851-21-2: 2021
Communication	
OCPP	OCPP 1.6J
Network Interface	Ethernet/4G/WiFi
RF Parameters	
LTE-FDD Operating Frequency	B1/B2/B3/B4/B5/B7/B8/B12/B13/B18/B19/B20/B25/B26/B28
LTE-TDD Operating Frequency	B38/B39/B40/B41
UMTS Operating Frequency	B1/B2/B4/B5/B6/B8/B19
MIFARE Operating Frequency	13.56MHz±7K
2.4G WI-FI Operating Frequency	2412MHz-2484MHz
2.4G WI-FI Maximum Transmit Power	20.5 dBm
WCDMA Maximum Transmit Power	24 dBm +1/-3 dB
LTE-FDD Maximum Transmit Power	23 dBm±2 dB
LTE-TDD Maximum Transmit Power	23 dBm±2 dB
MIFARE Maximum Transmit Power	14.05dBuA/m
Environment Condition	
Application Place	Indoor/Outdoor
Working Altitude	<2000m
Storage Temperature	-30℃~+85℃
Working Temperature	-30℃~+50℃
Working Humidity	5%~95%
Protection Level	IP55 IK10(Screen IK08)
Natural Cooling	Forced-air Cooling
Security Design	Over/Under Voltage Protection, Overload Protection, Current Leakage Protection, Grounding Protection, Over Temp Protection, Lightening Surge Protection

Model Selection

DC EV Charging Station		BDC300-F	BDC320-F	BDC330-F
				
Structure Description				
Shell Material	Galvanized Sheet			
Dimension	800*900*1900(L*W*H mm)			
Packing Dimension	1050*1250*2160(L*W*H mm)			
Weight	≤485kG	≤500kG	≤505kG	
Installation Method	Floor-stand Type			
Cable Routing	Bottom Inlet Wiring,Up Outlet Wiring			
Total length of gun cable	5 m			
Charging Outlets	Quadruple(A+B+C+D) (A:CCS1/CCS2/GBT/CHADEMO/NACS) (B:CCS1/CCS2/GBT/CHADEMO/NACS) (C:CCS1/CCS2/GBT/CHADEMO/NACS) (D:CCS1/CCS2/GBT/CHADEMO/NACS)			
Connectivity Authorization	RFID, App			
Screen	2*(7 Inch LCD Screen/LED Light)			
Electrical Specification				
AC Input Voltage	AC380V-415V, 3P+N+PE			
Rated Input Current	456A	587A	502A	
Input Frequency	50Hz/60Hz			
Consumption	≤24W			
Rated Power	300kW	320kW	330kW	
Output Voltage Range	CCS1/CCS2/NACS/GBT: 150Vdc ~ 1000Vdc;CHADEMO: 150Vdc ~ 500Vdc			
Output Current	CCS1/CCS2/NACS/GBT:0~250A;CHADEMO:0~125A			
Efficiency	≥95%			
Power Factor	≥0.99(load:100%)			

Functionate Design	
User Interface	Emergency Stop Button,LED Indicator,Card Swiping,Touch Screen
Charging Stands	EN IEC 61851-1: 2019, IEC 61851-1: 2017, EN 61851-23: 2014, IEC 61851-23: 2014, EN 61851-24: 2014, IEC 61851-24: 2014, EN IEC 61000-6-2: 2019, EN IEC 61000-6-4:2019, EN IEC 61851-21-2: 2021
Communication	
OCPP	OCPP 1.6J
Network Interface	Ethernet/4G/WiFi
RF Parameters	
LTE-FDD Operating Frequency	B1/B2/B3/B4/B5/B7/B8/B12/B13/B18/B19/B20/B25/B26/B28
LTE-TDD Operating Frequency	B38/B39/B40/B41
UMTS Operating Frequency	B1/B2/B4/B5/B6/B8/B19
MIFARE Operating Frequency	13.56MHz±7K
2.4G WI-FI Operating Frequency	2412MHz-2484MHz
2.4G WI-FI Maximum Transmit Power	20.5 dBm
WCDMA Maximum Transmit Power	24 dBm +1/-3 dB
LTE-FDD Maximum Transmit Power	23 dBm±2 dB
LTE-TDD Maximum Transmit Power	23 dBm±2 dB
MIFARE Maximum Transmit Power	14.05dBuA/m
Environment Condition	
Application Place	Indoor/Outdoor
Working Altitude	<2000m
Storage Temperature	-30℃~+85℃
Working Temperature	-30℃~+50℃
Working Humidity	5%~95%
Protection Level	IP55 IK10(Screen IK08)
Natural Cooling	Forced-air Cooling
Security Design	Over/Under Voltage Protection, Overload Protection, Current Leakage Protection, Grounding Protection, Over Temp Protection, Lightning Surge Protection

Model Selection

DC EV Charging Station		BDC360-F	BDC400-F	BDC440-F
				
Structure Description				
Shell Material	Galvanized Sheet			
Dimension	800*900*1900(L*W*H mm)			
Packing Dimension	1050*1250*2160(L*W*H mm)			
Weight	≤520kG	≤535kG	≤550kG	
Installation Method	Floor-stand Type			
Cable Routing	Bottom Inlet Wiring,Up Outlet Wiring			
Total length of gun cable	5 m			
Charging Outlets	Quadruple(A+B+C+D) (A:CCS1/CCS2/GBT/CHADEMO/NACS) (B:CCS1/CCS2/GBT/CHADEMO/NACS) (C:CCS1/CCS2/GBT/CHADEMO/NACS) (D:CCS1/CCS2/GBT/CHADEMO/NACS)			
Connectivity Authorization	RFID, App			
Screen	2*(7 Inch LCD Screen/LED Light)			
Electrical Specification				
AC Input Voltage	AC380V-415V, 3P+N+PE			
Rated Input Current	547A	608A	669A	
Input Frequency	50Hz/60Hz			
Consumption	≤24W			
Rated Power	360kW	400kW	440kW	
Output Voltage Range	CCS1/CCS2/NACS/GBT: 150Vdc ~ 1000Vdc;CHADEMO: 150Vdc ~ 500Vdc			
Output Current	CCS1/CCS2/NACS/GBT:0~250A;CHADEMO:0~125A			
Efficiency	≥95%			
Power Factor	≥0.99(load:100%)			

Functionate Design	
User Interface	Emergency Stop Button,LED Indicator,Card Swiping,Touch Screen
Charging Stands	EN IEC 61851-1: 2019, IEC 61851-1: 2017, EN 61851-23: 2014, IEC 61851-23: 2014, EN 61851-24: 2014, IEC 61851-24: 2014, EN IEC 61000-6-2: 2019, EN IEC 61000-6-4:2019, EN IEC 61851-21-2: 2021
Communication	
OCPP	OCPP 1.6J
Network Interface	Ethernet/4G/WiFi
RF Parameters	
LTE-FDD Operating Frequency	B1/B2/B3/B4/B5/B7/B8/B12/B13/B18/B19/B20/B25/B26/B28
LTE-TDD Operating Frequency	B38/B39/B40/B41
UMTS Operating Frequency	B1/B2/B4/B5/B6/B8/B19
MIFARE Operating Frequency	13.56MHz±7K
2.4G WI-FI Operating Frequency	2412MHz-2484MHz
2.4G WI-FI Maximum Transmit Power	20.5 dBm
WCDMA Maximum Transmit Power	24 dBm +1/-3 dB
LTE-FDD Maximum Transmit Power	23 dBm±2 dB
LTE-TDD Maximum Transmit Power	23 dBm±2 dB
MIFARE Maximum Transmit Power	14.05dBuA/m
Environment Condition	
Application Place	Indoor/Outdoor
Working Altitude	<2000m
Storage Temperature	-30°C~+85°C
Working Temperature	-30°C~+50°C
Working Humidity	5%~95%
Protection Level	IP55 IK10(Screen IK08)
Natural Cooling	Forced-air Cooling
Security Design	Over/Under Voltage Protection, Overload Protection, Current Leakage Protection, Grounding Protection, Over Temp Protection, Lightening Surge Protection

Model Selection

DC EV Charging Station		BDC480-F
		
Structure Description		
Shell Material	Galvanized Sheet	
Dimension	800*900*1900(L*W*H mm)	
Packing Dimension	1050*1250*2160(L*W*H mm)	
Weight	≤565kG	
Installation Method	Floor-stand Type	
Cable Routing	Bottom Inlet Wiring,Up Outlet Wiring	
Total length of gun cable	5 m	
Charging Outlets	Quadruple(A+B+C+D) (A:CCS1/CCS2/GBT/CHADEMO/NACS) (B:CCS1/CCS2/GBT/CHADEMO/NACS) (C:CCS1/CCS2/GBT/CHADEMO/NACS) (D:CCS1/CCS2/GBT/CHADEMO/NACS)	
Connectivity Authorization	RFID, App	
Screen	2*(7 Inch LCD Screen/LED Light)	
Electrical Specification		
AC Input Voltage	AC380V-415V, 3P+N+PE	
Rated Input Current	730A	
Input Frequency	50Hz/60Hz	
Consumption	≤24W	
Rated Power	480kW	
Output Voltage Range	CCS1/CCS2/NACS/GBT: 150Vdc ~ 1000Vdc;CHADEMO: 150Vdc ~ 500Vdc	
Output Current	CCS1/CCS2/NACS/GBT:0~250A;CHADEMO:0~125A	
Efficiency	≥95%	
Power Factor	≥0.99(load:100%)	

Functionate Design	
User Interface	Emergency Stop Button,LED Indicator,Card Swiping,Touch Screen
Charging Stands	EN IEC 61851-1: 2019, IEC 61851-1: 2017, EN 61851-23: 2014, IEC 61851-23: 2014, EN 61851-24: 2014, IEC 61851-24: 2014, EN IEC 61000-6-2: 2019, EN IEC 61000-6-4:2019, EN IEC 61851-21-2: 2021
Communication	
OCPP	OCPP 1.6J
Network Interface	Ethernet/4G/WiFi
RF Parameters	
LTE-FDD Operating Frequency	B1/B2/B3/B4/B5/B7/B8/B12/B13/B18/B19/B20/B25/B26/B28
LTE-TDD Operating Frequency	B38/B39/B40/B41
UMTS Operating Frequency	B1/B2/B4/B5/B6/B8/B19
MIFARE Operating Frequency	13.56MHz±7K
2.4G WI-FI Operating Frequency	2412MHz-2484MHz
2.4G WI-FI Maximum Transmit Power	20.5 dBm
WCDMA Maximum Transmit Power	24 dBm +1/-3 dB
LTE-FDD Maximum Transmit Power	23 dBm±2 dB
LTE-TDD Maximum Transmit Power	23 dBm±2 dB
MIFARE Maximum Transmit Power	14.05dBuA/m
Environment Condition	
Application Place	Indoor/Outdoor
Working Altitude	<2000m
Storage Temperature	-30°C~+85°C
Working Temperature	-30°C~+50°C
Working Humidity	5%~95%
Protection Level	IP55 IK10(Screen IK08)
Natural Cooling	Forced-air Cooling
Security Design	Over/Under Voltage Protection, Overload Protection, Current Leakage Protection, Grounding Protection, Over Temp Protection, Lightning Surge Protection