



Beny 2 Guns DC EV Charging Advertising Station

60kW-120kW



Datasheet

Zhejiang Benyi New Energy Co.,Ltd.

Shuanghuanglou Industrial Zone, Beibaixiang Yueqing,zhejiang P.R. China

TEL: +86-577-5717 7008 FAX: +86-577-5717 7007

✉ info@evb.com 🏠 Importer:xxxxxxx

🌐 www.evb.com 📍 Address:xxxxxxx

♻️ This catalogue has been printed on ecological paper .

© Zhejiang Benyi New Energy Co., Ltd. All rights reserved.

⚠️ If the models and specifications in this product catalogue change due to product updates, we will not provide prior notification.



VERSION: 20251229-01

WWW.EVB.COM

BENY

Product Overview

Remarkable 43-inch Advertising screen for effortless control. It comes with a range of certifications including CE, CB and RCM, and offers robust full protection features. With convenient app control and Ethernet/4G/WiFi connectivity, you can charge your EV with confidence and efficiency.



Product Advantages



IP65 Rating



Ethernet/4G/WiFi



Full Protection



OCPP 1.6J



43-inch
advertising screen



RFID



APP Control

Model Selection

DC EV Charging Station		BGDC60-D	BGDC90-D	BGDC120-D
				
Structure Description				
Shell Material		Galvanized Sheet		
Dimension		700*520*1800(L *W*H mm)		
Packing Dimension		1050*820*2035(L*W*H mm)		
Weight		≤330kG	≤350kG	≤370kG
Installation Method		Floor-stand Type		
Cable Routing		Bottom Inlet Wiring,Up Outlet Wiring		
Total length of gun cable		5 m		
Charging Outlets	Double(CCS1+CCS1)	Double (CCS2+CHADEMO)	Double (CCS1+NACS)	
	Double (CCS1+CHADEMO)	Double(CHADEMO+GBT)	Double(CCS2+NACS)	
	Double(CCS2+GBT)	Double(CCS1+CCS2)	Double(GBT+NACS)	
	Double(CHADEMO+CHADEMO)	Double(CCS1+GBT)	Double(CHADEMO+NACS)	
	Double(CCS2+CCS2)	Double(GBT+GBT)	Double(NACS+NACS)	
Connectivity Authorization		RFID, App		
Screen		43-Inch Advertising Screen/LED Light		
Electrical Specification				
AC Input Voltage		AC380V-415V,3P+N+PE		
Rated Input Current		102A	152A	203A
Input Frequency		50Hz/60Hz		
Consumption		≤40W		
Rated Power		60kW	90kW	120kW
Output Voltage Range		CCS1/CCS2/GBT/NACS: 150Vdc –1000Vdc;CHADEMO: 150Vdc –500Vdc		
Output Current		CCS1/CCS2:0~200A; GBT/NACS:0~200A; CHADEMO:0~125A	CCS1/CCS2:0~250A; GBT/NACS:0~250A; CHADEMO:0~125A	CCS1/CCS2:0~250A; GBT/NACS:0~250A; CHADEMO:0~125A
Efficiency		≥95%		
Power Factor		≥0.99(load:100%)		

Model Selection

Functionate Design	
User Interface	Emergency Stop Button,LED Indicator,Card Swiping,Touch Screen
Charging Stands	EN IEC 61851-1: 2019, IEC 61851-1: 2017, EN 61851-23: 2014, IEC 61851-23: 2014, EN 61851-24: 2014, IEC 61851-24: 2014, EN IEC 61000-6-2: 2019, EN IEC 61000-6-4:2019, EN IEC 61851-21-2: 2021
Communication	
OCPP	OCPP 1.6J
Network Interface	Ethernet/4G/WiFi
RF Parameters	
LTE-FDD Operating Frequency	B1/B2/B3/B4/B5/B7/B8/B12/B13/B18/B19/B20/B25/B26/B28
LTE-TDD Operating Frequency	B38/B39/B40/B41
UMTS Operating Frequency	B1/B2/B4/B5/B6/B8/B19
MIFARE Operating Frequency	13.56MHz±7K
2.4G WI-FI Operating Frequency	2412MHz-2484MHz
2.4G WI-FI Maximum Transmit Power	20.5 dBm
WCDMA Maximum Transmit Power	24 dBm +1/-3 dB
LTE-FDD Maximum Transmit Power	23 dBm±2 dB
LTE-TDD Maximum Transmit Power	23 dBm±2 dB
MIFARE Maximum Transmit Power	14.05dBuA/m
Environment Condition	
Application Place	Indoor/Outdoor
Working Altitude	<2000m
Storage Temperature	-30°C~~+55°C
Working Temperature	-30°C~~+50°C
Working Humidity	5%~95%
Protection Level	IP55 IK10(Screen IK08)
Natural Cooling	Forced-air Cooling
Security Design	Over/Under Voltage Protection, Overload Protection, Current Leakage Protection, Grounding Protection, Over Temp Protection, Lightning Surge Protection

Model Selection

DC EV Charging Station		BGDC120-D-350		
				
Structure Description				
Shell Material		Galvanized Sheet		
Dimension		700*520*1800(L*W*H mm)		
Packing Dimension		1050*820*2035(L*W*H mm)		
Weight		≤370kG		
Installation Method		Floor-stand Type		
Cable Routing		Bottom Inlet Wiring,Up Outlet Wiring		
Total length of gun cable		5 m		
Charging Outlets		Double(CCS1+CCS1) Double(CCS2+GBT) Double(CCS2+CCS2)	Double(CCS1+CCS2) Double(CCS1+GBT) Double(GBT+GBT)	Double (CCS1+NACS) Double(CCS2+NACS) Double(GBT+NACS) Double(NACS+NACS)
Connectivity Authorization		RFID, App		
Screen		43-Inch Advertising Screen/LED Light		
Electrical Specification				
AC Input Voltage		AC380V-415V,3P+N+PE		
Rated Input Current		203A		
Input Frequency		50Hz/60Hz		
Consumption		≤40W		
Rated Power		120kW		
Output Voltage Range		CCS1/CCS2/GBT/NACS: 150Vdc –1000Vdc		
Output Current		CCS1/CCS2/GBT/NACS:0~350A		
Efficiency		≥95%		
Power Factor		≥0.99(load:100%)		

Model Selection

Functionate Design		
User Interface		Emergency Stop Button,LED Indicator,Card Swiping,Touch Screen
Charging Stands		EN IEC 61851-1: 2019, IEC 61851-1: 2017, EN 61851-23: 2014, IEC 61851-23: 2014, EN 61851-24: 2014, IEC 61851-24: 2014, EN IEC 61000-6-2: 2019, EN IEC 61000-6-4:2019, EN IEC 61851-21-2: 2021
Communication		
OCPP		OCPP 1.6J
Network Interface		Ethernet/4G/WiFi
RF Parameters		
LTE-FDD Operating Frequency		B1/B2/B3/B4/B5/B7/B8/B12/B13/B18/B19/B20/B25/B26/B28
LTE-TDD Operating Frequency		B38/B39/B40/B41
UMTS Operating Frequency		B1/B2/B4/B5/B6/B8/B19
MIFARE Operating Frequency		13.56MHz±7K
2.4G WI-FI Operating Frequency		2412MHz-2484MHz
2.4G WI-FI Maximum Transmit Power		20.5 dBm
WCDMA Maximum Transmit Power		24 dBm +1/-3 dB
LTE-FDD Maximum Transmit Power		23 dBm±2 dB
LTE-TDD Maximum Transmit Power		23 dBm±2 dB
MIFARE Maximum Transmit Power		14.05dBuA/m
Environment Condition		
Application Place		Indoor/Outdoor
Working Altitude		<2000m
Storage Temperature		-30°C~~+55°C
Working Temperature		-30°C~~+50°C
Working Humidity		5%~95%
Protection Level		IP55 IK10(Screen IK08)
Natural Cooling		Forced-air Cooling
Security Design		Over/Under Voltage Protection, Overload Protection, Current Leakage Protection, Grounding Protection, Over Temp Protection, Lightning Surge Protection